

Wiertło do metalu KC



SWKC

- ▶ wiertło szlifowane o kącie 118 °
- ▶ wykonane ze stali szybkoobrotowej
- ▶ norma DIN 345
- ▶ uchwyt stożkowy Morse'a

SWKC-4,0	KC-4,0
SWKC-7,0	KC-7,0
SWKC-8,0	KC-8,0
SWKC-8,5	KC-8,5
SWKC-9,0	KC-9,0
SWKC-10,0	KC-10,0
SWKC-10,5	KC-10,5
SWKC-11,5	KC-11,5
SWKC-12,0	KC-12,0
SWKC-12,5	KC-12,5
SWKC-13,0	KC-13,0
SWKC-13,5	KC-13,5
SWKC-14,0	KC-14,0
SWKC-14,5	KC-14,5
SWKC-15,0	KC-15,0
SWKC-16,0	KC-16,0
SWKC-16,5	KC-16,5
SWKC-17,0	KC-17,0
SWKC-17,5	KC-17,5
SWKC-18,0	KC-18,0

SWKC-18,5	KC-18,5
SWKC-19,0	KC-19,0
SWKC-20,0	KC-20,0
SWKC-20,5	KC-20,5
SWKC-21,0	KC-21,0
SWKC-21,5	KC-21,5
SWKC-22,0	KC-22,0
SWKC-22,5	KC-22,5
SWKC-23,0	KC-23,0
SWKC-24,0	KC-24,0
SWKC-25,0	KC-25,0
SWKC-25,5	KC-25,5
SWKC-26,0	KC-26,0
SWKC-27,0	KC-27,0
SWKC-28,0	KC-28,0
SWKC-29,0	KC-29,0
SWKC-30,0	KC-30,0
SWKC-32,0	KC-32,0
SWKC-35,0	KC-35,0
SWKC-40,0	KC-40,0